

Summary

VIN:1HTLKTVR8KH671651

General Information

Customer Name: HERTZ-PENSKE TRUCK LEASING INC
Update ROUTE 10
READING, PA 19607

: DT466 INTL D/ENG 210HP@2600RPM 49-State, 210
Engine : HP @ 2600 RPM, 513 lb-ft Torque @ 1800 RPM
(0012482)

Application:

Model: F-1954 6X4

Engine
Serial 000564432
Number:

Repair Management Create Estimate

Unit No:

Edit

Inspection Exp:

Notes: No

OCC Authorization Form : N/A

Warranty Information

Order Date:

DTU Status: DTU

Build Date: 12/06/1988

DTU Miles: 10 Miles

Warranty Start Date: 03/26/1989

Standard
Warranty: Standard Warranty

Time In Service: 32 Years 8 Months

Diamond
Spec: No

DTU Engine Hours: 0

DTU Fuel
Used: 0.

Extended Warranty
Coverage: No

Managed Repair Information

Open Recalls: 1. 89505 SHEPP POWER STRG PITMAN
ARM (Open)

Open AFCs: No

Open MRCs: No

Open FSC: No



Calibration Status

BCM Status: Vehicle Calibration Scorecard

Electronic Feature(s): Vehicle Calibration Scorecard

Details

Vehicle Information

VIN : 1HTLKTVR8KH671651	Order Date :
Model : F-1954 6X4	Build Date : 12/06/1988
Engine :	DTU Date : 03/26/1989
Application Family :	Warranty Start Date : 03/26/1989
Application :	DTU Status : DTU
Wheel Base : 248.0	DTU Odometer : 10 Miles
DTU Engine Hours : 0	DTU Fuel Used : 0.
GVWR : 46000	Original Gear Ratio : 538
GCWR : 0	 Programmed Gear Ratio :
PC Number : 291207085	Order Number : 419145
Paint Color Code :	 After Frame : 103.0
Selling Dealer : <u>NAVISTAR, INC. (000132-000)</u>	Original Customer : HERTZ-PENSKE TRUCK LEASING INC
Customer : HERTZ-PENSKE TRUCK LEASING INC	Address : ROUTE 10
Address : ROUTE 10	City, State Zip : READING, PA 19607
City, State Zip : READING, PA 19607	
Toe (MM/M) N/A	
Forward Rear / Scrub (MM/M) N/A	
Rear Rear / Thrust (MM/M) N/A	

Components

Components

VIN : 1HTLKTVR8KH671651

56 components found. Export

S.No	Class Description	Part Number/Component	Manufacturer Part Drawing	Description
1	FRAMES	<u>0001143</u>	<u>0001143</u>	FRAME RAILS Heat Treated Alloy Steel (110,000 PSI Yield) 10.125" x 3.0625" x .3125" Includes Steel Front Bumper
2	FRAMES	<u>0001537</u>	<u>0001537</u>	FRAME REINFORCEMENT Outer C; Heat Treated Alloy Steel (110,000 PSI Yield) 10.720" x 3.310" x .25"
3	MISC	<u>0001910</u>	<u>0001910</u>	WHEELBASE, SPECIAL 2" Increments, in lieu of Advertised WB;
4	FRAMES	<u>0001950</u>	<u>0001950</u>	FRAME PIERCING
5	FRONT AXLES	<u>0002337</u>	<u>0002337</u>	AXLE, FRONT NON-DRIVING {Spicer I-120} 12,000-lb Capacity
6	BRAKES	<u>0004091</u>	<u>0004091</u>	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
7	BRAKES	<u>0004174</u>	<u>0004174</u>	BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 16 Sq. In. Brake Chambers
8	BRAKES	<u>0004273</u>	<u>0004273</u>	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30 Sq. In. MGM Spring Actuated Parking Brake Chambers
9	BRAKES	<u>0004550</u>	<u>0004550</u>	AIR COMPRESSOR {Bendix 501} 12 CFM
10	BRAKES	<u>0004786</u>	<u>0004786</u>	AIR DRYER {Bendix AD-4} with Heater,
11	STEERING	<u>0005331</u>	<u>0005331</u>	STEERING GEAR {Sheppard M-392} Power,
12	MISC	<u>0006722</u>	<u>0006722</u>	DRIVELINE CENTER BEARING (2)
13	ELECTRICAL SYSTEMS	<u>0008000</u>	<u>0008000</u>	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
14	ELECTRICAL SYSTEMS	<u>0008133</u>	<u>0008133</u>	ALTERNATOR {Delco Remy America Inc. 27SI Type 200} 12-Volt, 65-Amp. Capacity with Integral Regulator
15	ELECTRICAL SYSTEMS	<u>0008579</u>	<u>0008579</u>	CIRCUIT BREAKERS Auto-Reset (Main Panel) SAE Type II Replaces All Fuses Except Instrument Cluster Feed
16	ELECTRICAL SYSTEMS	<u>0008707</u>	<u>0008707</u>	INDICATOR, LOW OIL PRESSURE / HIGH COOLANT TEMPERATURE; Light & Audible Alarm
17	ELECTRICAL SYSTEMS	<u>0008723</u>	<u>0008723</u>	RADIO AM/FM Stereo with Multiple Speakers
18	ELECTRICAL SYSTEMS	<u>0008866</u>	<u>0008866</u>	BATTERIES (2) {Delco Remy America Inc. 1150} Maintenance-Free, 12-Volt, 1250 CCA
19	FRONT END	<u>0009107</u>	<u>0009107</u>	FRONT END Tilting, Fiberglass
20	FRONT END	<u>0009580</u>	<u>0009580</u>	RADIATOR STONE GUARD Bright Finish
21	SPEEDOMETER, TOOLS, MISC	<u>0010000</u>	<u>0010000</u>	SPEEDOMETER and Miscellaneous
22	SPEEDOMETER, TOOLS, MISC	<u>0010210</u>	<u>0010210</u>	LABEL Emissions, Fuel Economy and Noise. DO NOT ORDER-FOR FACTORY USE ONLY
23	SPEEDOMETER, TOOLS, MISC	<u>0010643</u>	<u>0010643</u>	PAINT IDENTITY, PT-2 Two Tone, Instruction No. 943. Wheels and Bumper
24	SPEEDOMETER, TOOLS, MISC	<u>0010758</u>	<u>0010758</u>	PAINT TYPE Base Coat/Clear Coat; TEST UNIT, Credit Code
25	SPEEDOMETER, TOOLS, MISC	<u>0010761</u>	<u>0010761</u>	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
26	CLUTCH	<u>0011370</u>	<u>0011370</u>	CLUTCH {Spicer SAS1402} Two-Plate, Stamped Angle Spring; Ceramic, 14" Diameter, 8-Spring Damper, with Mechanical Pull Type Control

27	ENGINE	<u>0012TSD</u>	<u>0012TSD</u>	FAN DRIVE {Schwitzer DD-26} Viscous
28	ENGINE	<u>0012482</u>	<u>0012482</u>	ENGINE, DIESEL {International DT-466C} 49-State, 210 HP @ 2600 RPM, 513 lb-ft Torque @ 1800 RPM
29	ENGINE	<u>0012914</u>	<u>0012914</u>	WARNING INDICATOR Low Coolant Level; Light and Audible Indicator
30	TRANSMISSION	<u>0013448</u>	<u>0013448</u>	TRANSMISSION, MANUAL {Fuller RT-6610} 10-Speed Manual, and With Air Shift
31	REAR AXLES, SUSPENSIONS	<u>0014475</u>	<u>0014475</u>	AXLE, REAR, TANDEM (Spicer J340-S) Single Reduction; 34,000-lb Capacity, with 190 Wheel Ends
32	REAR AXLES, SUSPENSIONS	<u>0014688</u>	<u>0014688</u>	SUSPENSION, REAR, TANDEM {Hendrickson U-340} Walking Beam Type 50" Axle Spacing; 34,000-lb Capacity
33	FUEL TANKS	<u>0015292</u>	<u>0015292</u>	FUEL TANK (2) Rectangular Steel, 51 U.S. Gal., 193 L Capacity (LT & RT) Includes Center Step; Total Capacity 102 U.S. Gal., 386 L
34	CABS, COWLS, BODIES	<u>0016000</u>	<u>0016000</u>	FLOOR COVERING Transmission Cover, Floor Mats and Seal DO NOT ORDER-FOR FACTORY USE ONLY
35	CABS, COWLS, BODIES	<u>0016030</u>	<u>0016030</u>	CAB Conventional, Day Cab
36	CABS, COWLS, BODIES	<u>0016335</u>	<u>0016335</u>	SEAT, DRIVER {National Cush-N-Aire} Air Suspension, Low Back, Chestnut Vinyl, Isolated
37	CABS, COWLS, BODIES	<u>0016430</u>	<u>0016430</u>	SEAT, PASSENGER {International} Non-Suspension, Low Back, Chestnut Vinyl
38	CABS, COWLS, BODIES	<u>0016651</u>	<u>0016651</u>	WINDSHIELD WIPERS (2) Air, with Single Motor; Cowl Mounted
39	CABS, COWLS, BODIES	<u>0016660</u>	<u>0016660</u>	GLASS, ALL WINDOWS Tinted
40	CABS, COWLS, BODIES	<u>0016686</u>	<u>0016686</u>	MIRRORS (2) Rectangular, West Coast Type, Aluminum Head & Brackets, 16" x 7" Size, 102" Spacing, Satin Finish
41	CABS, COWLS, BODIES	<u>0016956</u>	<u>0016956</u>	AIR CONDITIONER {International Blend-Air} With Integral Heater
42	WHEELS, TIRES - FRONT	<u>0027523</u>	<u>0027523</u>	WHEELS, FRONT DISC; 22.5" Painted Steel, 10-Stud (11.25" BC) 8.25 DC Rims; With Steel Hubs
43	WHEELS, TIRES - REAR	<u>0028523</u>	<u>0028523</u>	WHEELS, REAR DUAL DISC; 22.5" Painted Steel, 10-Stud (11.25" BC) 8.25 DC Rims; With Steel Hubs
44	WHEELS MISC OPTIONS	<u>0029580</u>	<u>0029580</u>	WHEEL SEALS, FRONT {International} Oil-Lubricated Wheel Bearings
45	WARRANTY	<u>0040010</u>	<u>0040010</u>	WARRANTY Medium Duty Standard 12 Months
46		<u>0088250</u>	<u>0088250</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
47		<u>0090250</u>	<u>0090250</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
48		<u>0260DTA</u>	<u>0260DTA</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
49		<u>0260DTL</u>	<u>0260DTL</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
50		<u>0260054</u>	<u>0260054</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
51		<u>0730213</u>	<u>0730213</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
52		<u>0770213</u>	<u>0770213</u>	*** ERROR GETTING DECSRIPTION: SQLCODE = +00100
53	FUEL TANKS	<u>0845505</u>	<u>0845505</u>	FUEL/WATER SEPARATOR {ConMet CM99-327D} with Heater & Sight Glass.
54	CABS, COWLS, BODIES	<u>0846205</u>	<u>0846205</u>	HEATER HOSES {International} Premium.
55		<u>0882513</u>	<u>0882513</u>	*** ERROR GETTING DECSRIPTION: SQLCODE

56

0902513

0902513

=+00100

*** ERROR GETTING DECSRIPTION: SQLCODE

=+00100